

43  
Amended

a pneumatically operated variable diameter pinch valve for controlling the flow rate of the granular mold flux from the intermediate hopper through the delivery tube, the pinch valve including a rubber sleeve through which the granular mold flux passes, and a source of air and a pressure control valve to vary the diameter of the rubber sleeve between fully closed, fully open, and a plurality of intermediate positions so that the flow rate of the granular mold flux through the delivery tube may be varied.

46

5. (Amended) The apparatus for introducing granular mold flux onto the top of a slab being cast within a continuous casting mold as set forth in claim 3 wherein there is a single delivery tube assembly, the delivery tube having discharge branches which can deliver granular mold flux to either side of a ceramic pouring tube.

47

8. (Amended) The apparatus for introducing granular mold flux onto the top of a slab being cast within a continuous casting mold as set forth in claim 1 wherein the diameter of the pinch valve is optimally 1 inch, and the diameter of the delivery tube is at least 1 inch.

12. (Amended) Apparatus for introducing granular mold flux onto the top of a slab being cast within a continuous casting mold; the apparatus comprising:

a source of granular mold flux;

delivery means to deliver the granular mold flux from the source to the top of a slab being cast within the continuous casting mold, the delivery means including at least one delivery tube assembly including a flexible line, and an inline air pump which assures a positive flow of granular mold flux through the flexible line, and

AS  
a variable diameter pinch valve for controlling the flow rate of the granular mold flux from the intermediate hopper through the delivery tube, the pinch valve including a rubber sleeve through which the granular mold flux passes, and means to vary the diameter of the rubber sleeve between fully closed, fully open, and a plurality of intermediate positions so that the flow rate of the granular mold flux through the delivery tube may be varied.

13. (Amended) The apparatus for introducing granular mold flux onto the top of a slab being cast within a continuous casting mold as set forth in claim 12 wherein there is a single delivery

tube assembly, the delivery tube having discharge branches which can deliver granular mold flux to either side of a ceramic pouring tube, the delivery branches being downstream of the inline air pump.

14. (Amended) Apparatus for introducing granular mold flux onto the top of a slab being cast within a continuous casting mold; the apparatus comprising:

a source of granular mold flux;

an intermediate hopper which receives granular mold flux from the source; and

one or more delivery tube assemblies interconnected with the intermediate hopper for insuring the feeding of the granular mold flux from the intermediate hopper to the top of the slab being cast within the continuous casting mold, each delivery tube assembly including a flexible line, and an inline air pump which assures a positive flow of granular mold flux through the flexible line.

In the abstract:

Apparatus for introducing granular mold flux onto the top of a slab being cast within a continuous casting mold, the apparatus having delivery apparatus for feeding granular mold flux from an intermediate hopper to the top of the slab being cast, the